

Suspension Grade Magnesium Oxide For Plant Food

Fertilizer Formulation Guide

To ensure blending performance when using CropMag[®] 200 in conjunction with orthophosphates for suspension formulations, the following guidelines are recommended:

1. On a grade basis, keep the phosphate level at or below 12% $\mathsf{P}_2\mathsf{O}_5.$ Keep the magnesium level at or below 2.5% Mg.

Example: A 16-8-8 2.5% Mg will blend satisfactorily (the phosphate and the magnesium levels are within the recommended guideline above).

Example: A 5-15-20 3.1% Mg at 400 lb/acre should be reduced to 4-12-16 2.5% Mg and applied at 500 lb/acre to meet the above guideline.

2. The total equivalent water should be at least 35% of the mix, or 700 lb/ton. (Equivalent water is equal to actual water plus 1/3 of the 10-30-0 plus ½ the nitrogen solution).

Example: 12-9-12 2.5% Mg

Order of Addition (lb/ton)	Equivalent Water
293 Water (free)	293
87 CropMag 200	
600 10-30-0	200
35 Clay	
600 Nitrogen Solution (30%)	300
<u>385</u> Potash	
2000	793 = 39.5%

3. CropMag 200 should be dispersed in free water when possible. If there is not enough free water in the formulation, CropMag 200 can be added after the nitrogen solution, but before the potash (see order of addition above).

The addition of other fertilizer materials, such as calcium, zinc, manganese, and especially ammonium sulfate and polyphosphates, may require that trial "bucket batches" be mixed to determine acceptable levels of viscosity.

NOTICE: THE INFORMATION CONTAINED HEREIN IS, TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ACCURATE. ANY RECOMMENDATIONS OR SUGGESTIONS MADE ARE WITHOUT WARRANTY OR GUARANTEE OF RESULTS SINCE CONDITIONS OF HANDLING AND OF USE ARE BEYOND OUR CONTROL; WE THEREFORE, ASSUME NO LIABILITY FOR LOSS OR DAMAGE INCURRED BY FOLLOWING THESE SUGGESTIONS. SELLER WARRANTS ONLY THAT THIS PRODUCT WILL MEET THE SPECIFICATIONS SET FORTH. ANY OTHER REPRESENTATION OR WARRANTY, EITHER EXPRESS OR IMPLIED, IS SPECIFICALLY DISCLAIMED INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND OF MERCHANTABILITY. SELLERS AND MANUFACTURERS ONLY OBLIGATION SHALL BE TO REPLACE SUCH QUANTITY OF THE PRODUCT FOR USERS INTENDED APPLICATION AND USER ASSUMES ALL RISK AND LIABILITY WARRANTES OF FITNESS FOR A PARTICULAR SUITABILITY OF THE PRODUCT FOR USERS INTENDED APPLICATION AND USER ASSUMES ALL RISK AND LIABILITY WARRANTES OF FITNESS FOR A PARTICULAR CONTRACT OR UNDER ANY THEORY FOR ANY LOSS OR DAMAGE, INCIDENTAL OR CONSEQUENTIAL, ARISING OUT OF THE USE OF OR THE INABILITY TO USE THE PRODUCT.

Martin Marietta Magnesia Specialties, LLC

2700 Wycliff Road, Suite 320 Raleigh, North Carolina 27607 USA Phone: (800) 648-7400 www.magnesiaspecialties.com



Produced under a Quality Management System certified to ISO 9001:2015 by PRI Certification Registrar