

MATERIAL SAFETY DATA SHEET

361UF

| | |
|--|--|
| MARTIN MARIETTA MAGNESIA SPECIALTIES 8140 Corporate Drive, Suite 220 BALTIMORE, MD 21236 (410) 780-5500 | MSDS CODE: 5100UF DATE: November 20, 2009 |
| | EMERGENCY PHONE: 800-424-9300 CHEMTREC |
| CHEMICAL DESCRIPTION: Oil based fuel additive with Magnesium Hydroxide | |
| PRODUCT NAME(S): FireShield UF | |

SECTION II: HAZARDOUS COMPONENTS

| HAZARDOUS COMPONENT | CAS NUMBER | ACGIH/OSHA EXPOSURE LIMIT |
|----------------------|------------|---------------------------|
| Magnesium Hydroxide | 01309-42-8 | None established |
| Fuel Oil | 68476-34-6 | 200 ppm |
| Tall Oil, Fatty Acid | 61790-12-3 | None established |

SECTION III: PHYSICAL DATA

| | |
|---|-----------------------------------|
| BOILING POINT (F): Not determined | FREEZE POINT (F): Not determined |
| pH: Not determined | VAP PRESS (mm Hg): Not determined |
| % VOLATILE (by VOL): Not determined | SPECIFIC GRAVITY: ~ 1.4 at 75 F |
| VAPOR DENSITY: Not determined | EVAPORATION RATE: Not determined |
| SOLUBILITY IN WATER: Negligible | ODOR THRESH (ppm): Not determined |
| PHYSICAL STATE: Liquid | OIL/WATER COEFFIC: Not determined |
| APPEARANCE AND ODOR: Pink liquid slurry, fuel oil odor. | |

SECTION IV: FIRE & EXPLOSION DATA (con't on page 2)

| | | |
|--|-----------------------------------|--------------|
| FLASH POINT (METHOD): ~ 142 F (ASTM D-93 Pensky-Martin Closed Cup) | | |
| AUTO-IGNITION TEMP: Not determined | LEL: Not det | UEL: Not det |
| SENSITIVE TO MECHANICAL IMPACT? No | SENSITIVE TO STATIC DISCHARGE? No | |

DATE: 02-25-2003

PRODUCT: FireShield UF

MSDS CODE:5100UF

SECTION IV: FIRE & EXPLOSION DATA (con't From page 1)

EXTINGUISHING MEDIA:

Dry chemical and carbon dioxide. Foam and water fog are also effective, but may cause frothing if sprayed into hot or burning product.

SPECIAL FIREFIGHTING PROCEDURES:

Do not enter enclosed or confined spaces without NIOSH approved organic vapor respirator or self-contained breathing apparatus for protection against combustion products or oxygen deficiencies. If possible to do so safely, shut off product at source. Use caution when spraying water to cool container surfaces exposed to heat or flame as frothing may occur, especially if water is sprayed into hot or burning product.

UNUSUAL FIRE & EXPLOSION HAZARDS:

When heated above its flash point, this product may release hazardous or flammable vapors which can burn in open spaces or collect to create a potentially explosive condition in enclosed spaces. Mists or sprays may be flammable at temperatures below the normal flash point.

SECTION V: REACTIVITY DATA

STABLE - YES: XX

NO:

CONDITIONS OF REACTIVITY:

Product may react with incompatibles listed below.

INCOMPATIBILITY (MATERIALS TO AVOID):

Strong oxidizers such as, but not limited to, sodium hypochlorite, chromic acid, hydrogen peroxide, bromine, liquid chlorine or liquid oxygen.

HAZARDOUS DECOMPOSITION PRODUCTS:

May produce smoke, carbon monoxide, and/or carbon dioxide during combustion.

IS THIS PRODUCT SUBJECT TO POLYMERIZATION?

NO: XX

YES:

CONDITIONS UNDER WHICH PRODUCT WILL POLYMERIZE:

None known.

DATE: 02-25-2003

PRODUCT: FireShield UF

MSDS CODE:5100UF

SECTION VII: PREVENTATIVE MEASURES

GLOVES:

Oil impervious gloves if frequent or prolonged contact is expected.

EYES:

Safety goggles or chemical splash goggles, especially if splashing is anticipated.

CLOTHING:

Wear body covering work clothes to avoid prolonged or repeated exposure. Change clothing frequently if contaminated with product. Launder soiled work clothes before re-using.

RESPIRATORY PROTECTION:

Under ambient conditions, normally none required. If high vapor or mist concentrations are expected, use NIOSH approved respirator for organic vapors.

SPECIFIC ENGINEERING CONTROLS TO BE USED WITH THIS PRODUCT:

This material has a low vapor pressure and is not expected to present an inhalation hazard at ambient conditions. However, if vapor is generated as the product is heated, misted, or sprayed, adequate ventilation in accordance with good engineering practices must be provided to maintain concentrations below the specified exposure or flammable limits.

PROCEDURES TO FOLLOW IN CASE OF SPILL OR LEAK:

Immediately remove all sources of ignition. If possible to do so safely, shut off product at source. Ventilate enclosed space and use appropriate respiratory protection. Contain spill and prevent product from entering all bodies of water. Evacuate all non-essential personnel from immediate area due to slippery conditions. Clean up spilled product, including any soil or water which is contaminated, as soon as possible, with pump (explosion proof motor) or absorb with vermiculite, sand or similar inert material. Reclaim product for possible re-use or collect and seal in approved containers for disposal in an appropriate manner.

DISPOSAL PROCEDURE: Dispose in accordance with local, state and federal regs.

SECTION VII: PREVENTATIVE MEASURES

HANDLING PROCEDURES AND EQUIPMENT:

Keep container closed when not in use. Use in well ventilated area. Store in a cool location well away from strong oxidizers and building exits. Take precautions to eliminate sources of ignition such as open flames, pilot lights, or welding equipment. Never use a cutting torch on or near product or empty drum containing any residue of this product.

| | | |
|------------------|------------------------|------------------|
| DATE: 02-25-2003 | PRODUCT: FireShield UF | MSDS CODE:5100UF |
|------------------|------------------------|------------------|

PREVENTATIVE MEASURES (con't. From page 4)

| | | |
|---|------------------------|---------------|
| <p>STORAGE REQUIREMENTS: Consumption of food and beverages should be avoided in work areas where product is being used. After using product, always wash hands and face with soap and water before eating, drinking or smoking.</p> | | |
| DOT SHIP NAME: Fuel oil mixture. | CLASS: Combustible liq | UN#: UN 1993 |
| NFPA - FIRE:1 OTHER: | HEALTH:1 | REACTIVITY: 0 |
| <p>SARA: None of the components in this product are reportable under Section 302 or Section 313 of SARA Title III.</p> | | |
| <p>TSCA: All components of this product are on the TSCA inventory list.</p> | | |

SECTION VIII: FIRST AID PROCEDURES

| |
|---|
| <p>INHALATION: If overcome by vapor or mist from heated or sprayed product, immediately remove from exposure and call a physician. If breathing is irregular or has stopped, start resuscitation and administer oxygen, if available.</p> |
| <p>EYE CONTACT: Do not rub eyes. Flush eyes with clear water for at least fifteen (15) minutes while rotating eyes in every direction to ensure that no solid particles remain in creases of eyelids. If so, continue to flush. If irritation persists, consult an ophthalmologist.</p> |
| <p>SKIN CONTACT: Remove from source of irritation. Remove any contaminated clothing and wash affected area(s) thoroughly with a mild soap and water. Launder clothing before re-using. If irritation persists, consult a physician.</p> |
| <p>INGESTION: Due to possibility of aspiration into lungs, DO NOT induce vomiting. Keep exposed person at rest and immediately call a physician.</p> |

SECTION IX: PREPARATION INFORMATION

| | | |
|----------------------------|-----------------------|--------------------------|
| PREPARED BY: Linda Aydlett | PHONE: (410) 780-5548 | DATE PREPARED:02-25-2003 |
|----------------------------|-----------------------|--------------------------|

